

# Overvoltage protection socket strip 5-fold with ext. protective earth conductor

Item-No.: 0206x0005230101 (1,5 m cord)



Robust plastic, grey

Built-in sockets (90° rotated), round

Extra large space in between sockets 64 mm

1,5 m power cord and angle plug (optional with 3 m or 5 m power cord)


Expanded contact protection by using a shutter

End caps with mounting possibility and spare fuse

Acoustic and optical trigger signal



EHMANN advantage - the connected devices will remain in operation after release of overvoltage protection

EHMANN advantage - extended protection against accidental contact through additional external protective earth conductor



## Overvoltage protection socket strip 5-fold with ext. protective earth conductor

Technical data

3.600 W Power	250 V ~ / 50 Hz Rated voltage	16 A Rated current
<p>Power Cord: H05VV-F 3G 1,5 mm<sup>2</sup>            Plug: CEE 7/7 plug Type EF, angled            Sockets: earthing contact Type F            Switch: 2-pole, illuminated (red)            Consumption per switch: &lt; 0,4 W            Voltage U<sub>n</sub>: 230 V~            Max. continuous operation voltage U<sub>c</sub>: 255 V~            U<sub>oc</sub>: 5000 V            Protection level Up: L-N &lt; 1,0kV - L/N-PE &lt; 1,5kV            I<sub>max</sub> (8/20): 6,5 kA            Fuse: T6,3AH/250 V            SPD according to EN 61643-11: Type 3            Consumption overvoltage protection: &lt; 0,1 W            Earth conductor: ring cable lug 4,2x 1,5 mm<sup>2</sup>, length approx. 1 m            Safety class: IP20</p>		
 <p>(similar illustration)</p>		
<p>Item-No. 0206x0005230101 (1,5 m cord)    EAN 401209600580 3    PU10</p>		<p>462 x 74 x 47 mm            Dimensions (L x W x H)            454 mm            Fixing Dimension</p>