

# Overvoltage protection socket strip 5+2-fold with external push button

Item-no.: 0206x00072381 (1,5 m cord)



Robust plastic, grey

Built-in sockets (90° rotated), round

Extra large space in between sockets 64 mm

1,5 m power cord and angle plug

5 black, switchable sockets and 2 grey, permanent sockets

External hand- and foot push button with 2 m flexible cord and signal lamp

Push button prevents unintended restart after e.g. power failure

Easy connectable and/or exchangeable push button via RJ12 connector

Expanded contact protection by using a shutter

End caps with mounting possibility



Acoustic fault message

EHMANN advantage - the connected devices will remain in operation after release of overvoltage protection



## Overvoltage protection socket strip 5+2-fold with external push button

Technical data

3.600 W Power	250 V~ / 50 Hz Rated voltage	16 A Rated current
<p>Power cord: H05VV-F 3G 1,5 mm<sup>2</sup>            Plug: CEE 7/7 plug type EF, angular            Sockets: Earthing contact type F            Uoc: 5000 V            Protection level Up: L-N &lt; 1,0kV - L/N-PE &lt; 1,5kV            I<sub>max</sub> (8/20): 6,5 kA            SPD according to EN 61643-11: Type 3            Push button: pluggable (RJ12-socket, 6-polar)            Consumption overvoltage protection: 0,7 W (off), 1,8 W (on)            Safety class: IP20</p>		
 <p>(similar illustration)</p>		
Item-no. 0206x00072381 (1,5 m)	EAN 401209600421 9	PU 25
654 x 74 x 47 mm Dimensions (L x W x H) 582 mm Fixing Dimension		