

RCD / personal protection socket strip 4-fold with switch

Item-no.: 0221x00042301 (1,5 m cord) | 0221x00042303 (3 m cord) | 0221x00042305 (5 m cord)



Robust plastic, grey

Built-in sockets (90° rotated), round

Extra large space in between sockets 64 mm

1,5 m power cord and angle plug (optional with 3 m or 5 m power cord)

Personal protection through RCD (30 mA)





Expanded contact protection by using a shutter

End caps with mounting possibility



RCD / personal protection socket strip 4-fold with switch

Technical data

3.600 W Power	250 V ~ / 50 Hz Rated voltage	16 A Rated current
Power cord: H05VV-F 3G 1,5 mm ² Plug: CEE 7/7 plug, angular type EF Sockets: earthing contact type F Switch: 2-pole, illuminated Personal Protection: RCD (30 mA) Own Consumption: < 0,5 W Safety class: IP20		  
 <p>(similar illustration)</p>		
Item-no. 0221x00042301 (1,5 m) Item-no. 0221x00042303 (3 m) Item-no. 0221x00042305 (5 m)	EAN 401209602323 4 EAN 401209600619 0 EAN 401209600650 3	PU 20 PU 10 PU 10 462 x 74 x 47 mm Dimensions (L x W x H) 454 mm Fixing dimension