

## LED flush-mounted dimmer T39.07 / T39.07.1

Item-no.: 3900x0700ch / 3900x0710ch





Suitable for dimmable LED lamps, incandescent, HV- and NV halogen lamps

Opportunities for optimized and flicker-free dimming of LED lamps in min. area

Short-circuit, overload and over-temperature protection

No stand-by consumption because of a real on/off switch

With (3900x0710ch) or without (3900x0700ch) Swiss mounting frame

EHMANN advantage - 100% quality checks, 5 years warranty, German manufacturer

EHMANN service - Up to date LED recommendation accessible via imprinted QR-code at any time

EHMANN quality - High-grade manufacturing and reliable function













## LED flush-mounted dimmer T39.07 / T39.07.1

## Technical data

| 3 - 35 W<br>LED rated power   | 7 - 110 W/VA<br>Rated power  | 230 V ~ (+/- 10%) / 50 Hz<br>Rated voltage |
|---|--|--|
| Suitable for dimmable LED lamps, in   | ncandescent, HV-, and NV-halogen lar   | mps with magnetic transformer              |
| Operation principle: Leading edge   |  |  |
| Function: rotation dimmer with pres   | ssure two-way switch   |  |
| Shaft: Ø 4 mm metal shaft with fine   | raster   |  |
| Connection: Screw terminals up to 2 x 2,5 mm <sup>2</sup> (rigid)   |  | R,L  |
| Temperature protection: thermal fu  | ise  |  |
| Short-circuit/overload protection: Fine fuse T1AH/250V  |  | REACH   RoHS                               |
| (incl. spare fuse)  |  |  |
| Tuning possibilities for flicker-<br>free dimming of LED lamps<br>In case of flickering during dimming the<br>LED lamp you can try to adjust in the | LED recommendation Shows which LEDs are compatible with this dimmer. Available via QR code or online at www.ehmann-gmbh.de |  |
| lowest dimming range the minimum brightness and try to optimise the dimming behaviour.  |  |  |
| Item-no. 3900x0700ch EAN 40 1209  | 6 00652 7 PU 10  | 59 x 33 mm                                 |