

# LED flush-mounted dimmer T39.08 / T39.08.1

Item-no.: 3900x0800ch / 3900x0810ch





Suitable for dimmable LED lamps, incandescent, HV- and NV- halogen lamps

Opportunities for optimized and flicker-free dimming of LED lamps in min. area

Short-circuit, overload and over-temperature protection

No stand-by consumption because of a real on/off switch

With (3900x0810ch) or without (3900x0800ch) Swiss mounting frame

EHMANN advantage - 100% quality checks, 5 years warranty, German manufacturer

EHMANN service - Up to date LED recommendation accessible via imprinted QR-code at any time

EHMANN quality - High-grade manufacturing and reliable function













## LED flush-mounted dimmer T39.08 / T39.08.1

### Technical data

3 - 85 W LED rated power

20 - 250 W/VA Rated power 230 V ~ (+/- 10%) / 50 Hz rated voltage

Suitable for dimmable LED lamps, incandescent, HV-, and NV-halogen lamps with magnetic transformer

Operation principle: Leading edge

Function: rotation dimmer with pressure two-way switch

Shaft: Ø 4 mm metal shaft with fine raster

Connection: Screw terminals up to 2 x 2,5 mm<sup>2</sup> (rigid)

Temperature protection: thermal fuse

Short-circuit/overload protection: Fine fuse T2AH/250V

(incl. spare fuse)



















#### Tuning possibilities for flickerfree dimming of LED lamps

In case of flickering during dimming the LED lamp you can try to adjust in the lowest dimming range the minimum brightness and try to optimise the dimming behaviour.





#### LED recommendation

Shows which LEDs are compatible with this dimmer. Available via QR code or online at www.ehmann-gmbh.de



Item-no. 3900x0800ch Item-no. 3900x0810ch EAN 401209600663 3 EAN 401209600184 3 PU 10 PU 10 59 x 33 mm Dimensions (ø x H)