

LED flush-mounted dimmer T46.03 / T46.03.1

Item-no.: 4600x0300ch / 4600x0310ch



Suitable for dimmable LED lamps, dimmable LED driver, incandescent and HV- and NV-halogen lamps

SILENT TECHNOLOGY - Operates utterly quiet

Opportunities for optimized and flicker-free dimming of LED lamps in max. area

Electronically controlled short-circuit, overload and over-temperature protection with automatic reactivation

No stand-by consumption because of a real on/off switch

With (4600x0310ch) or without (4600x0300ch) Swiss mounting frame

EHMANN advantage - 100 % quality assurance, 5 years warranty, German manufacturer




EHMANN service - Up to date LED recommendation accessible via imprinted QR-code at any time

EHMANN quality - High-grade manufacturing and reliable function



LED flush-mounted dimmer T46.03 / T46.03.1

Technical data

| | | |
|---|---|--|
| <p>3 - 50 W LED rated power</p> | <p>15 - 150 W/VA Rated power</p> | <p>230 V ~ (+/- 10%) / 50 Hz rated voltage</p> |
| <p>Suitable for dimmable LED lamps, dimmable LED driver, incandescent and HV-halogen lamps with electronic transformer</p> | | |
| <p>Operating principle: trailing edge Function: rotation dimmer with pressure two-way switch Shaft: Ø 4 mm metal shaft with fine raster Connection: screw terminals up to 2 x 2,5 mm² (rigid) Temperature protection: resettable thermal switch Short-circuit/overload protection: electronic</p> | |  |
| <p>Tuning possibilities for flicker-free dimming of LED lamps In case of flickering during dimming the LED lamp, you can try to adjust in the highest dimming range the maximum brightness to optimise the dimming behaviour.</p>  | <p>LED recommendation Shows which LEDs are compatible with this dimmer. Available via QR code or online at www.ehmann-gmbh.de</p>  | |
| <p>Item-no. 4600x0300ch EAN 401209600662 6 PU 10 Item-no. 4600x0310ch EAN 401209600185 0 PU 10</p> | | <p>59x 33 mm Dimensions (ø x H)</p> |