

LED flush-mounted dimmer T46.08 / T46.08.1

Item-no.: 4600x0800ch / 4600x0810ch



Suitable for dimmable LED lamps, dimmable LED driver, incandescent and HV-halogen lamps with electronic transformer

SILENT TECHNOLOGY - Operates utterly quiet

Optimisation possibilities for flicker-free dimming of LED lamps in min. and max. area

Electronically controlled short-circuit, overload and over-temperature protection with automatic reactivation

No stand-by consumption because of a real on/off switch

With (4600x0810ch) or without (4600x0800ch) Swiss mounting frame

EHMANN advantage - 100 % quality assurance, 5 years warranty, German manufacturer






EHMANN service - Up to date LED recommendation accessible via imprinted QR-code at any time

EHMANN quality - High-grade manufacturing and reliable function



LED flush-mounted dimmer T46.08 / T46.08.1

Technical data

<p>5 - 150 W LED rated power</p>	<p>15 - 450 W/VA Rated power</p>	<p>230 V ~ (+/- 10%) / 50 Hz rated voltage</p>
<p>Suitable for dimmable LED lamps, dimmable LED driver, incandescent and HV-halogen lamps with electronic transformer</p>		
<p>Operating principle: trailing edge Function: rotation dimmer with pressure two-way switch Shaft: Ø 4 mm metal shaft with fine raster Connection: screw terminals up to 2 x 2,5 mm² (rigid) Temperature protection: resettable thermal switch Short-circuit/overload protection: electronic</p>		  
<p>Tuning possibilities for flicker-free dimming of LED lamps In case of flickering during dimming the LED lamp, you can try to adjust in the lowest and highest dimming range the minimum and maximum brightness to optimise the dimming behaviour.</p> 	<p>LED recommendation Shows which LEDs are compatible with this dimmer. Available via QR code or online at www.ehmann-gmbh.de</p> 	
<p>Item-no. 4600x0800ch EAN 4012096006596 PU 10 Item-no. 4600x0810ch EAN 4012096006619 PU 10</p>		<p>59 x 33 mm Dimensions (ø x H)</p>