

Master-slave PRO permanent socket strip 5+2-fold with overvoltage protection

Item-no.: 0215x00078301 (1,5 m cord)



Robust plastic, grey

Built-in sockets (90° rotated), round

1,5 m power cord and angle plug (optional with 3 m or 5 m power cord)

1 blue master socket, 4 black slave sockets and 2 gray permanent sockets

Automatic electronic switching M/S with precisely adjustable switching threshold


Optical function display for M/S function

Acoustic fault message in case of overvoltage protection according to EN 61643-11 type 3

EHMANN advantage - the connected devices will remain in operation after release of overvoltage protection



Expanded contact protection by using a shutter

End caps with mounting possibility and spare fuse



Master-slave PRO permanent socket strip 5+2-fold with overvoltage protection

Technical data

3.600 W Power	250 V ~ / 50 Hz Rated voltage	16 A Rated current	
Power cord: H05VV-F 3G 1,5 mm ² Plug: CEE 7/7 plug type EF, angular Sockets: Earthing contact type F Voltage U _n : 230 V~ Max. continuous operation voltage U _c : 255 V~ U _{oc} : 5000 V Protection level Up: L-N < 1,0kV - L/N-PE < 1,5kV I _{max} (8/20): 6,5 kA Fuse: T6,3AH/250 V SPD according to EN 61643-11: Type 3 Precise switching threshold: 7-100 W (master) Consumption: < 0,6 W Consumption overvoltage protection: < 0,1 W Safety class: IP20			
 <p>(similar illustration)</p>			
Item-no. 0215x00078301	EAN 401209600749 4	PU 10	590 x 74 x 47 mm Dimensions (L x W x H) 582 mm Fixing dimension