

Master-slave PRO socket strip 4-fold with USB-A

Item-no.: 0216x0a048301 (1,5 m cord)



Robust plastic, grey

Built-in sockets (90° rotated), round

1,5 m power cord and angle plug (optional with 3 m or 5 m power cord)

Automatic electronic switching M/S with precisely adjustable switching threshold


Optical function display for M/S function

USB-A double-port (slave) with max. 2,1 A each with intelligent control of charging current

Expanded contact protection by using a shutter



End caps with mounting possibility

Output overcurrent limitation and output overvoltage protection, checked according to EN 62368, EN55032, IEC61000 and EN 55024



Master-slave PRO socket strip 4-fold with USB-A

Technical data

3.600 W Power	230 V ~ (+/- 10%) / 50 Hz Rated voltage	16 A Rated current
<p>Power cord: H05VV-F 3G 1,5 mm² - 1,5m length Plug: CEE 7/7 plug type EF, angular Sockets: Earthing contact type F Precise switching threshold: 7-100 W (master) USB: 2-fold charger,</p> <p>AC voltage range: 100-240 V AC, 50/60Hz Output voltage: 5V DC Charging current: max. 2,1 A (per 2-fold charger) Compatible: Apple, Android, Google, etc.</p> <p>Consumption: < 0,6 W Safety class: IP20</p>		
 <p>(Similar illustration)</p>		
Item-no. 0216x0a048301	EAN 401209600750 0	PU 10 462 x 74 x 47 Dimensions (L x W x H) 454 mm Fixing dimensions (X)