

Flush-mounted dimmer T46.05

Item-no.: 4600x0500



Suitable for incandescent-, HV- and LV-halogen lamps with electronic transformer

Compatible with common switch ranges from GIRA, Busch Jäger, Berker, Jung etc.

SILENT TECHNOLOGY - Operates utterly quiet

Opportunities for optimized and flicker-free dimming in min. and max. area

Electronically controlled short-circuit, overload and over-temperature protection with automatic reactivation

No stand-by consumption because of a real on/off switch

EHMANN advantage - 100 % quality assurance, 5 years warranty, German manufacturer




EHMANN service - Switch range adapter included

EHMANN quality - High-grade manufacturing and reliable function



Flush-mounted dimmer T46.05

Technical data

<p>20 - 550 W/VA Rated power</p>	<p>230 V ~ (+/- 10%) / 50 Hz Rated voltage</p>	
<p>Suitable for incandescent-, HV- and LV-halogen lamps with electronic transformer</p>		
<p>Operating principle: Trailing edge Function: rotation dimmer with pressure two-way switch Shaft: metal shaft \varnothing 4 mm with fine raster (\varnothing 6 mm with shaft adapter) Connection: screw terminals up to 2 x 2.5 mm² (rigid) Temperature protection: resettable thermal switch Overload/short-circuit protection: electronic</p>		
<p>Switch range adapter Allows the use of common covers e.g. Gira, Busch-Jäger, Jung, Berker</p> 	<p>Tuning possibility for flicker-free dimming In case of flickering during dimming, you can try to adjust in the lowest and highest dimming range the minimum and maximum brightness to optimize the dimming behavior.</p> <p>Min Max</p> 	
<p>Item-no. 4600x0500 EAN 401209646005 3 PU 10</p>	<p>71 x 71 x 33 mm Dimension (L x W x H)</p>	