

## EHMANN workshop socket strip 4+1-fold

Master/slave function for the comfortable operation of dependent devices (vacuuming)

Item-no.: 0266x00059301 (1,5 m cord)



Robust plastic, grey

Built-in sockets (90° rotated), round

2x master sockets in blue for tools (saw, drill machine, etc.)

2x slave sockets in black for vacuuming device(s)

1x permanent socket in grey (light, etc.)

Adjustable lead time and follow-up time for individual control of vacuuming devices (slaves)

Lead time: time-shifted activation of the slave sockets (overload protection at the starting torque)

Follow-up time: delayed deactivation of the slave sockets (pipe cleaning, no short interruptions)

1,5 m power cord and angle plug



Expanded contact protection by using a shutter

End caps with mounting possibility



## EHMANN workshop socket strip 4+1-fold

### Technical data

3.600 W Power	230 V ~ (+/- 10%) / 50 Hz Rated voltage	16 A Rated current
<p>Power cord: H05VV-F 3G 1,5 mm<sup>2</sup>, 1,5 meters</p> <p>Plug: CEE 7/7 plug type EF, angular type</p> <p>Sockets: earthing contact type F with touch protection</p> <p>Safety class: IP20</p> <p>Switching threshold master/slave: min. 40W</p> <p>Lead-time shift: adjustable from 0-7 seconds</p> <p>Follow-up delay: adjustable from 0-7 seconds</p> <p><b>Please note:</b> The permitted total power of master and slave must not exceed the stated power of 3.600W!</p>		
 <p>(similar illustration)</p>		
<p>Item-no. 0266x00059301 (1,5 m cord)    EAN 4012096007999    PU 10</p>		<p>462 x 74 x 47 mm Dimensions (L x W x H)</p> <p>454 mm Fixing dimension (X)</p>