

Blind switch ROLLO2.0 Comfort 24 with frame

Item-no.: 6660x0500



Ready-to-install device with frame

Easy programming within three seconds

Week programme: Blind will be operated at the same time every day of the week (daily repetition)

Manual control at any time through push button

Microprocessor controlled

With child lock / Programme lock

Possibility for external connection for group switching, twilight switch, wind sensors, time switch and other 230 V signal transmitter

Backup programme in case of power supply loss

For flush-mounted switch boxes up to Ø 65 mm

EHMANN advantage - 100 % quality checks, 5 years warranty, German manufacturer









Blind switch ROLLO2.0 Comfort 24 with frame

Technical data

750 VA
switching capacity

230 V ~ (+/- 10%) / 50 Hz Rated voltage White (similar to RAL 9010) Colour

Built-in device with standard central plate (operator keys / 50 x 50 mm), incl. decorative ring, standard intermediate frame and cover

Operation:

Short actuation of the corresponding button activates the blind (to the maximum extent). Pushing again stops the blind at the current position. After 180 seconds (maximum extent) the drives will be disconnected from the power supply.

Programming:

Week programme: Pushing on the button for 3 seconds programmes the daily operation or its daily repetition (24h automatic / LED blinks red).

Loss of power supply:

Programmes will be saved for one hour should a loss of power supply occur

Connection: screw clamps

Contact opening: µ



Optical signal of the week programme (red LED blinks)









Item-no. 6660x0500

EAN 401209600563 6

PU 10

 $82 \times 82 \times 32 \, mm$ Dimensions (L x W x installation depth)