

Blind switch ROLLO2.0 Comfort 24

Item-no.: 6660x0600



Easy programming within three seconds

Week programme: Blind will be operated at the same time every day of the week (daily repetition)

Manual control at any time through push button

Microprocessor controlled

With child lock / programme lock

Possibility for external connection for group switching, twilight switch, wind sensors, time switch and other 230 V signal transmitter

Back up programme in case of power supply loss

For flush-mounted switch boxes up to Ø 65 mm

For implementation in customary switch ranges with inner dimensions of 50x50 mm (you might have to use intermediate frames for standard devices)

EHMANN advantage - 100 % quality checks, 5 years warranty, German manufacturer









Blind switch ROLLO2.0 Comfort 24

Technical data

750 VA switching capacity	230 V ~ (+/- 10%) / 50 Hz Rated voltage	White (similar to RAL 9010) Colour
---------------------------	--	--

Operation:

Short actuation of the corresponding button activates the blind (to the maximum extent). Pushing again stops the blind at the current position. After 180 seconds (maximum extent) the drives will be disconnected from the power supply.

Programming:

Week programme: Pushing the button for 3 seconds programmes the daily operation or its daily repetition (24h automatic / LED blinks red).

Loss of power supply:

Programmes will be saved for one hour should a loss of power supply occur

Built-in device with standard central plate (operation keys / 50 x 50 mm)

Connection: screw clamps

Contact opening: µ

