

Blind switch ROLLO2.0 Comfort 24/7 with frame

Item-no.: 6661x0500



Ready-to-install device with frame

Easy programming of week and day programme

Week programme: Blind will be operated at the same time every day of the week (daily repetition)

Day programme: Each day of the week can be programmed differently

Manual control at any time through push button

Microprocessor controlled

With child lock / programme lock

Possibility for external connection for group switching, twilight switch, wind sensors, time switch and other 230 V signal transmitter

Back up programme in case of power loss







For flush-mounted switch boxes up to Ø 65 mm

EHMANN advantage - 100 % quality checks, 5 years warranty, German manufacturer



Blind switch ROLLO2.0 Comfort 24/7 with frame

Technical data

| | | |
|--|---|---|
| 750 VA switching capacity | 230 V ~ (+/- 10%) / 50 Hz Rated voltage | White (similar to RAL 9010) Colour |
| Built-in device with standard central plate (operator keys / 50 x 50 mm), incl. decorative ring, standard intermediate frame and cover | | |
| <p>Operation: Short actuation of the corresponding button activates the blind (to the maximum extent). Pushing again stops the blind at the current position. After 180 seconds (max. extent) the drives will be disconnected from the power supply.</p> <p>How to programme: Week programme: Pushing the button for 3 seconds programmes the daily operation or its daily repetition (24h automatic / LED blinks red).</p> <p>Day programme: Pushing the button for 8 - 15 seconds programmes a separate day (e.g. weekend / LED blinks green).</p> <p>Loss of power supply: Programmes will be saved for 72 hours should a loss of power supply occur</p> <p>Connection: screw clamps</p> <p>Contact opening: μ</p> | | |
|  <p>Optical signal of the week programme (red LED blinks)</p> |  <p>Optical signal of the day programme (green LED blinks)</p> |     |
| Item-no. 6661x0500 | EAN 401209600565 0 | PU 10 82 x 82 x 32 mm Dimensions (L x W x installation depth) |