

# Aluminum master-slave PRO socket strip 4-fold with USB-C

Item-no.: 0616x0g048001 (1,5 m cord)



Noble, transparent anodized aluminum case, matt

1 USB-C Port 18W (5V 3A, 9V 2A, 12V 1.5A@18W Max) with output voltage regulation

Built-in sockets (90° rotated), round

1,5 m power cord and angle plug


Automatic electronic switching M/S with precisely adjustable switching threshold

Optical function display for M/S function

Expanded contact protection by using a shutter



End caps with mounting possibility

Output overcurrent limitation and output overvoltage protection, checked according to EN 62368, EN55032, IEC61000 and EN 55024



## Aluminum master-slave PRO socket strip 4-fold with USB-C

### Technical data

3.600 W Power	230 V ~ (+/- 10%) / 50 Hz Rated voltage	16 A Rated current
Power cord: H05VV-F 3G 1,5 mm <sup>2</sup> - 1,5m length Plug: CEE 7/7 plug type EF, angular Sockets: Earthing contact type F Precise switching threshold: 7-100 W (master) USB-C: 1-fold charger, AC voltage range:       100-240 V AC, 50/60Hz Charging power:        18W max Consumption: < 0,6 W Safety class: IP20		
 <p>(similar illustration)</p>		
Item-no. 0616x0g048001	EAN 4012096010197	PU10  458 x 65 x 44 Dimensions (L x W x H) 452 mm Fixing dimension (X)