

Universal socket strip 3-fold (type G)

Item-no.: 0200x0603230b-1 (1.5 m cord) | 0200x0603230b-3 (3 m cord)



Robust plastic, grey

Built-in sockets (90° rotated), quadrangular

Extra large space in between sockets 64 mm

1.5 m power cord and angle plug (optional with 3 m power cord)



Expanded contact protection

End caps with mounting possibility



Universal socket strip 3-fold (type G)

Technical Data

| 3000 W Power | 230 V ~ (+/- 10%) / 50 Hz Rated voltage | 13 A Rated current | | | | | | |
|---|--|---|-------------------|-------|-------------------------------------|-------------------|-------|--|
| Power cord: H05VV-F 3G 1.5 mm ² Plug: BP1 British Standard Type G, BS 1363/A, angled Fuse: 13A fuse according to BS 1362 Sockets: Type G Safety class: IP20 | |  | | | | | | |
|  <p>(similar illustration)</p> | | | | | | | | |
| <table border="0"> <tr> <td>Item-no. 0200x0603230b-1 (1,5 m cord)</td> <td>EAN 4012096010968</td> <td>PU 10</td> </tr> <tr> <td>Item-no. 0200x0603230b-3 (3 m cord)</td> <td>EAN 4012096010951</td> <td>PU 10</td> </tr> </table> | | Item-no. 0200x0603230b-1 (1,5 m cord) | EAN 4012096010968 | PU 10 | Item-no. 0200x0603230b-3 (3 m cord) | EAN 4012096010951 | PU 10 | 270 x 74 x 47 mm Dimensions (L x W x H) 262 mm Fixing dimension |
| Item-no. 0200x0603230b-1 (1,5 m cord) | EAN 4012096010968 | PU 10 | | | | | | |
| Item-no. 0200x0603230b-3 (3 m cord) | EAN 4012096010951 | PU 10 | | | | | | |